## **Material Safety Data Sheet**

# **Section 1: Product Information**

Manufacturer's Name / Address: **Trade Name:** 4750 Lava Flow Color

Packs

Versatile Building Products Colorant **Chemical Family:** 

245 Carl Karcher Way Anaheim, CA 92801 Info. Phone: 714-829-2600

> **Intended Use:** Decorative Colorant

24 Hour Emergency Phone: INFOTRAC (800) 535-5053

**Initial Issue Date:** 7/11/12 **Revision Date:** NA Prepared By: M. Glendrange

#### **Section 2: Hazardous Ingredients**

**Hazardous Component** % (Optional) **OSHA PEL ACGIH TLV Other Limits** 

Mica Polymer

VOC of Component: 0g/L VOC As Applied:0g/L

## Section 3: Physical Data

ND 3.0 **Boiling Point (°C): Specific Gravity:** 

NA **Melting Point:** Decomposes Vapor Pressure:

Vapor Density: NA **Evaporation Rate:** NA

(Air = 1)(Butyl Acetate = 1)

Solubility in Water: Insoluble 4-8 pH:

Freezing Point NA

Coefficient of Oil/Water Distribution:

Off white with no significant odor **Appearance and Odor:** 

**Odor Threshold:** NE

#### **Section 4: Fire and Explosion Hazard**

ND Flash Point (°C): **Conditions of Flammability:** NA

Flammable Limits: LEL: NE UEL: NE

**Autoignition Temperature (°C):** 

**Hazardous Combustion Products:** Carbon dioxide, carbon monoxide if polymer is burning.

Sensitivity to Impact: None Sensitivity to Static Discharge:

**Extinguishing Media:** Carbon dioxide, water spray if polymer is burning.

**Special Firefighting Procedures:** No special procedure. Product as supplied is non-combustible.

**Unusual Fire and Explosion** Combustable vapors may form if exposed to excessive heat during fire.

Hazards:

Page 2 of 4 Material Safety Data Sheet Product: 4750 Lava Flow Color Packs

Section 5: Health Hazard Data					
Primary R	outes of Entry:   Eye Inhalation Skin Contact Ingestion				
	<b>ure Effects</b> : Inhalation of pulverized flake dust may cause irritation in the respiratory tract.				
	Aggravated by Exposure: None known.				
Health Haz	zards (Acute and Chronic Exposures):				
Eyes					
A	cute:				
M	Iay cause irritation.				
C	hronic:				
N	one known.				
Skin Conta	act .				
A	cute:				
N	lay cause irritation.				
C	hronic:				
N	fone known.				
Skin Absor	ption				
	cute:				
N	D				
C	hronic:				
	D				
Inhalation					
	cute:				
	fay cause irritation.				
	hronic:				
	fone known.				
Ingestion	one and min				
_	cute:				
	D				
	hronic:				
	D				
1,					
Emergency	and First Aid Procedures:				
General:					
Remove eff	ected person from area. Treat symptomatically.				
Eyes:					
Flush with water for 15 minutes. Seek medical assistance if symptoms persist.					
Skin:					
Remove soiled clothing. Flush skin with water for 15 minutes.					
Inhalation:					
Remove effected person to fresh air away from the product. Give assisted respiration if breathing has stopped, or					
becomes labored. Seek medical attention immediately.					
Ingestion:					
	ician immediately. Remove stomach contents by gastric suction or induce vomiting only as directed by				
medical personnel.					
mearear per					
Carcinoger	nic Data:				
NTP: No					
OSHA: No					
IARC: No					
Toxicologic	ral Data:				
ND	van ac 111111				
*					

Page 3 of 4 Material Safety Data Sheet Product: 4750 Lava Flow Color Packs

Section 6: Reactivity Data	Section	6:	Reactivity	Data
----------------------------	---------	----	------------	------

Chemical Stability: ⊠ Stable ☐ Unstable

Conditions to Avoid: ND

mpatibi lity (Materials to Avoid): ND

**Hazardous Decomposition Products**: CO, CO2, and oxides of nitrogen if combusted.

Hazardous Polymerization (Reactivity) : ☐ May Occur ☑ Will Not Occur

# Section 7: Spill and Leak Procedures:

Steps to be Taken in Case of Material Release or Spillage: Sweep spilled product. Prevent entry into waterways.

Waste Disposal Method: Dispose in accordance with local, state, and federal regulation.

**Ecological Information**: ND

**Ecotoxicity**: ND

## **Section 8: Special Protection Information**

Engineering Controls: General and local exhaust.

Respiratory Protection: Particle dust mask should be worn when handling product.

Protective Gloves: Nitrile or butyl rubber.

Eye Protection: Splash proof goggles or chemical goggles should be worn when handling product.

Other protective Equipment: Clothing that will cover exposed skin. Emergency showers and eye wash stations should

be readily accessible.

# **Section 9: Handling and Storage**

General: Store between 50-100F in dry area.

# **Section 10: Supplemental Information**

**Health**: 0 Flammability: 0 Reactivity: 0

**DOT Proper Shipping Name**: Not DOT Regulated

Hazard Class : NA UN Number: NA Packing Group: NA

IMO Shipping Data: Refer to Bill of Lading. ICAO/IATA Shipping Data: Not IATA Regulated

TSCA (Toxic Substance Control Act):

All components are listed in the TSCA chemical substance inventory. CERCLA (Comprehensive Response Compensation and Liability Act):

ND

**SARA Title III**:

ND

**California Proposition 65**: Below is a list of compounds known to the State of California to cause cancer, birth defects, or other reproductive harm:

ND

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the accuracy of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers and users of this product must comply with all applicable health and safety laws, regulations and orders.