# **Material Safety Data Sheet**

## **Section 1: Product Information**

Manufacturer's Name / Address: Trade Name: 4920 Joint Filler A-Comp.

Versatile Building Products Chemical Family: Polyol mixture

245 Carl Karcher Way Anaheim, CA 92801

Info. Phone: Intended Use: Architectural Joint Filler

714-829-2600

**24 Hour Emergency Phone:** INFOTRAC (800) 535-5053

Initial Issue Date: 8/9/7 Revision Date: NA Prepared By: P. Dalvi

# **Section 2: Hazardous Ingredients**

Hazardous Component	OSHA PEL	ACGIH TLV	Other Limits	% (Optional)
Amine Polyol mixture	NE	NE	NE	80-90
Exempt Solvent Mixture	NE	NE	NE	10-20

VOC of Component: 0g/L VOC As Applied:0 g/L

## **Section 3: Physical Data**

 Boiling Point (°C):
 ND
 Specific Gravity:
 1.0-1.1

 Vapor Pressure:
 ND
 Melting Point:
 NE

 Vapor Density:
 ND
 Evaporation Rate:
 <1</td>

 (Air = 1)
 (Butyl Acetate = 1)

Solubility in Water: Partial pH: ND

Freezing Point ND

Coefficient of Oil/Water Distribution: ND

Appearance and Odor: Clear to cloudy clear w/ solvent odor.

Odor Threshold: ND

# Section 4: Fire and Explosion Hazard

Flash Point (°C): 56 Conditions of Flammability: NA

Flammable Limits: LEL: ND UEL: ND

Autoignition Temperature (°C): ND

Hazardous Combustion Products: Carbon monoxide, carbon dioxide, NOx, Ammonia

Sensitivity to Impact: None

Sensitivity to Static Discharge: May ignite product.

**Extinguishing Media:** Dry foam and chemicals, carbon dioxide, water.

Special Firefighting Procedures: Use self-contained breathing apparatus and impermeable clothing. Unusual Fire and Explosion Heated containers may rupture. Cool containers with water spray.

Hazards:

Page 2 of 4 Material Safety Data Sheet Product: 4920 Polyurea Joint Filler A-Comp.

# **Section 5: Health Hazard Data**

**Primary Routes of Entry:** ⊠ Eye ⊠ Inhalation ⊠ Skin Contact X Ingestion

Overexposure Effects: Dizziness, nausea, headaches, drowsiness, unconciousness and death.

Conditions Aggravated by Exposure: Existing skin dermatitis and rashes may be aggravated by exposure.

### **Health Hazards (Acute and Chronic Exposures):**

Eyes

Acute:

None

Chronic:

ND

#### **Skin Contact**

Acute:

Irritation, redness, and pain.

Chronic:

ND

#### **Skin Absorption**

Acute: ND

Chronic:

ND

#### Inhalation

Acute:

Irritation of the respiratory tract. Labored breathing. Dizziness, headache, unconciousness, and death.

Chronic

Kidney damage and severe pulmonary injury may occur.

#### Ingestion

Acute:

Irritation of the gastrointestinal tract. Nausea.

Chronic:

ND

### **Emergency and First Aid Procedures:**

### General:

Treat symptomatically. If not breathing administer artificial respiration.

#### Eyes:

Immediatley rinse eyes with a direct stream of water for 15 minutes while holding the eyelids open. Seek medical attention if symptoms persist.

#### Skin:

Remove contaminated clothing, jewelry and shoes. Immediately wash contaminated skin with abundant water and mild soap. I f symptoms persist seek medical advice.

### Inhalation:

Remove effected person to fresh air. Administer artificial respiration if not breathing and unconcious. Give oxygen if breathing is labored. Seek medical attention.

### Ingestion:

DO NOT INDUCE VOMITING. Seek medical attention immediatley.

### Carcinogenic Data: NTP: Not regulated OSHA: Not regulated

**OSHA**: Not regulated **IARC**: Not regulated

#### **Toxicological Data:**

Based on most toxic component: Oral LD50 >2000g/kg. Dermal-slight to moderate irritant

Page 3 of 4 Material Safety Data Sheet Product: 4920 Polyurea Joint Filler A-Comp.

Section 6: Reactivity Data				
Chemical Stability: Stable Conditions to Avoid: Excessive heat	Unstable and cold.			
mpatibility (Materials to Avoid)	: Strong oxidizers, concentrated acids.			
Hazardous Decomposition Products: From combustion: Carbon monoxide, carbon dioxide, NOx				
Hazardous Polymerization (Reactivity) : May Occur Will Not Occur				

# **Section 7: Spill and Leak Procedures:**

**Steps to be Taken in Case of Material Release or Spillage**: Evacuate non-essential personnel. Remove sources of ignition. Ventilate area. Contain spill. Notify proper authorities as necessary. Cover spill with absorbant material. Collect spill in appropriate waste container.

Waste Disposal Methods: Dispose of material in accordance with local, state and federal regulation.

**Ecological Information**: Low potential to effect aquatic organisms. Low potential to bioconcentrate.

**Ecotoxicity**: Based on most hazardous component: 96-h LC-50 (fathead minnow) : 66 mg/L 48 - h EC50(dphnid): 88.6 mg/L

# **Section 8: Special Protection Information**

**Engineering Controls**: Ventilation to maintain TWA and STEL exposure limits. Shut off all open sources of ignition. **Respiratory Protection**: NIOSH approved repirator capable of filtering organic solvents must be worn when handling product.

**Protective Gloves**: Neoprene ro butyl rubber gloves must be worn when handling the product. NO Vinyl gloves. **Eye Protection**: Chemical goggles or face shield must be worn when handling the product. Use of contact lenses is not advised.

**Other protective Equipment**: Eye wash station and emergency shower should be in close proximity to areas where product is being handled. Impermeable clothing should be worn. Clean contaminated clothing before reuse.

# **Section 9: Handling and Storage**

**General**: Store away from open sources of ignition, excessive heat, excessive cold, oxidizers, strong acids; store in well ventilated areas.

# **Section 10: Supplemental Information**

Health: 2 Flammability: 2 Reactivity: 1

DOT Proper Shipping Name: Polyol mixture solution

Hazard Class: Non-Regulated UN Number: Non-Regulated

Packing Group: NA

IMO Shipping Data: Non-Regulated

ICAO/IATA Shipping Data: Non-Regulated

### TSCA (Toxic Substance Control Act):

All components of this product are listed in the TSCA inventory.

CERCLA (Comprehensive Response Compensation and Liability Act):

Reportable quantity Xylene (CAS# 1330-20) 100lbs

**SARA Title III:** 

Section 311/312 Immediate health hazard, . Section 313 Reportable Ingredients: None

**California Proposition 65**: Below is a list of compounds known to the State of California to cause cancer, birth defects, or other reproductive harm:

None

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the accuracy of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers and users of this product must comply with all applicable health and safety laws, regulations and orders.